

Reciprocity-based DMISO in dynamic multipath environments

P. Bidigare


18 August 2014

Introduction

Motivation for Coherent Distributed Communications


- **Why Coherent Distributed MIMO?**
 - Longer ranges and/or higher data rates
 - Simple augmentation by adding more nodes, graceful degradation with node loss
 - Smaller size, weight and power and cost radios
 - Interference resistant
- **Why Now?**
 - \$1.2T/year cellular market has developed cheap, highly capable radio ICs.
 - Logisitics enabled by proliferation of small-SWaP SDR radios

MIMO Communications Taxonomy



Pon Arrays 101

Retrodirective array with arbitrary antenna element locations.




Classic Pon Array

- Mixing by twice the carrier frequency does signal conjugation.
- Signal conjugation is the narrow-band equivalent of time reversal.

Classic (1964) Pon Array

- CW reference produces:



- Mixing by twice the carrier conjugates signal.

$$\cos\left(\omega\left(t - \frac{\|\mathbf{x}_n\|}{c}\right)\right)\cos(2\omega t) = \frac{1}{2}\cos\left(\omega\left(t + \frac{\|\mathbf{x}_n\|}{c}\right)\right) + \frac{1}{2}\cos\left(\omega\left(3t - \frac{\|\mathbf{x}_n\|}{c}\right)\right)$$

filtered out

- Reflected signals add up coherently at reference

$$v(\mathbf{x}, t) = \sum_{n=1}^{N_p} \cos\left(\omega\left(t + \frac{\|\mathbf{x}_n\|}{c} - \frac{\|\mathbf{x} - \mathbf{x}_n\|}{c}\right)\right)$$


$$v(\mathbf{0}, t) = N_p \cos(\omega t)$$

Pon array limitations


- **Not fully distributed:**
 - **Arbitrary phase center locations but**
 - **Common local oscillator required**
- **Retrodirectively beamformed signal is not arbitrary: it's the spectral inverse of what was received**
- **Beamforming is degraded by multipath**
- **Requires identical unit-to-unit hardware component delays**

Distributed Retrodirective Beamforming


Retrodirection with stationary, single-path propagation




Linear time-invariant device and propagation modeling



Retrodirective Beamforming Cycle



Retrodirective Beamforming: Stationary Case



1. **Bob** and **Charlie** transmit known ranging waveforms to **Alice**
2. **Alice** estimates the channels and computes “SYNC” equalizers for these

$$H_{\text{Chan}}^{\text{BA}} = H_{\text{Clock}}^{\text{B}} H_{\text{TX}}^{\text{B}} H_{\text{Prop}}^{\text{BA}} H_{\text{RX}}^{\text{A}} \overline{H}_{\text{Clock}}^{\text{A}}$$

$$H_{\text{Chan}}^{\text{CA}} = H_{\text{Clock}}^{\text{C}} H_{\text{TX}}^{\text{C}} H_{\text{Prop}}^{\text{CA}} H_{\text{RX}}^{\text{A}} \overline{H}_{\text{Clock}}^{\text{A}}$$

$$H_{\text{SYNC}}^{\text{BA}} = 1/H_{\text{Chan}}^{\text{BA}} \quad H_{\text{SYNC}}^{\text{CA}} = 1/H_{\text{Chan}}^{\text{CA}}$$

3. **Alice** broadcasts the equalizers to **Bob** and **Charlie**
4. **Tanya** transmits unknown waveform to **Alice**, **Bob** and **Charlie**
5. **Alice** rebroadcasts **Tanya's** waveform to **Bob** and **Charlie**
6. **Bob** and **Charlie** compute the “TDOA” filter which, when applied to the signal received directly from **Tanya**, produces the rebroadcast signal seen from **Alice**

$$H_{\text{TDOA}}^{\text{TB}} = H_{\text{Chan}}^{\text{TA}} H_{\text{Chan}}^{\text{AB}} / H_{\text{Chan}}^{\text{TB}} \quad H_{\text{TDOA}}^{\text{TC}} = H_{\text{Chan}}^{\text{TA}} H_{\text{Chan}}^{\text{AC}} / H_{\text{Chan}}^{\text{TC}}$$

7. **Bob** and **Charlie** compute “BF” filters as the products of their SYNC and TDOA filters.



$$H_{\text{BF}}^{\text{TB}} = H_{\text{Chan}}^{\text{TA}} H_{\text{Chan}}^{\text{AB}} / H_{\text{Chan}}^{\text{TB}} H_{\text{Chan}}^{\text{BA}} \quad H_{\text{BF}}^{\text{TC}} = H_{\text{Chan}}^{\text{TA}} H_{\text{Chan}}^{\text{AC}} / H_{\text{Chan}}^{\text{TC}} H_{\text{Chan}}^{\text{CA}}$$

8. **Alice**, **Bob** and **Charlie** transmit a common signal to **Tayna**. **Bob** and **Charlie** precompensate using their BF filters. After propagation, the signals add constructively

$$H_{BF}^{TB} H_{Chan}^{BT} = H_{Chan}^{TA} H_{Chan}^{AB} H_{Chan}^{BT} / H_{Chan}^{TB} H_{Chan}^{BA} = H_{Chan}^{TA}$$

$$H_{\text{BF}}^{\text{TC}} H_{\text{Chan}}^{\text{CT}} = H_{\text{Chan}}^{\text{TA}} H_{\text{Chan}}^{\text{AC}} H_{\text{Chan}}^{\text{CT}} / H_{\text{Chan}}^{\text{TC}} H_{\text{Chan}}^{\text{CA}} = H_{\text{Chan}}^{\text{TA}}$$

Similarity with other techniques



Time-reversal based retrodirective beamforming:

$$H_{\text{TR-BF}}^{\text{TB}}(f) = H_{\text{Chan}}^{\text{TA}}(f) H_{\text{Chan}}^{\text{AB}}(f) H_{\text{Chan}}^{\text{TB}}(-f) H_{\text{Chan}}^{\text{BA}}(-f)$$


Our retrodirective beamforming technique:

$$H_{\text{BF}}^{\text{TB}}(f) = \frac{H_{\text{Chan}}^{\text{TA}}(f) H_{\text{Chan}}^{\text{AB}}(f)}{H_{\text{Chan}}^{\text{TB}}(f) H_{\text{Chan}}^{\text{BA}}(f)}$$

[1] D.R. Brown III and A.G. Klein. [Timestamp-Free Network Synchronization with Random Pairwise Message Exchanges](#). Proceedings of the 39th International Conference on Acoustics, Speech, and Signal Processing (ICASSP2014). Florence, Italy, May 4-9, 2014.


[2] David F. Smith, Anis Husain U.S. Patent 8743976 [Techniques and systems for communications based on time reversal pre-coding](#). Filed: September 3, 2010 Issued: June 3, 2014

Simulation results with Rician fading channels




Retrodirective Beamforming Block Diagram

Coordinating Node Processing



Subordinate Node Processing



Coop-BF and Retro-BF Processing

Retro-BF Only Processing

Open Questions

- **What approximations to the zero-forcing equalizer filters are suitable for**
 - Channel estimation errors
 - Finite impulse response filters with constrained numbers of taps
 - Low peak-to-average power ratio (PAPR) waveforms
- **Can we generalize this technique beyond the star topology presented here?**
- **How can we make use of measurements between subordinate nodes (Bob $\Leftrightarrow$ Charlie)?**
- **Is there a generalization to the MIMO case?**
- **How can feedback-based nullforming be integrated with retrodirective beamforming?**
- **How can dynamic channels be parsimoniously modeled?**
- **what filters are suitable for predicting these?**
- **Are there a theoretical advantages of retrodirective beamforming over feedback-based beamforming?**
- **What are the fundamental limits of retrodirective beamforming performance as a function of wavelength, clock and motion and update rate?**