

Uplink User-Assisted Distributed Relaying for Cellular Communications

Ahmad Abu Al Haija, Hussain ElKotby, Mai Vu

Electrical and Computer Engineering
Tufts University

18 August 2014

Presentation DMIMO Summit, WPI



Research areas

- Research areas
 - Wireless communications, network communications
 - Signal processing, applied optimization
- Recent topics
 - MIMO precoding and capacity
 - Cognitive radio and cognitive networks
 - Cooperative communications
- Current directions
 - Future cellular systems (4G, 5G)
 - Ad hoc network communications

Students whose work is in this talk



Ahmad Abu Al Haija




Hussain ElKotby

Uplink User-Assisted Cooperative Relaying in Cellular Networks


Context

- 2G/3G cellular systems
 - Resource partitioning – connections are single-user links
 - Spectral efficiency per link approaches the theoretical limit
- Future high data rate demands
- 4G solutions
 - Small (femto) cells
 - Multi-cell processing
 - D2D communication
- 5G ideas
 - More small cells (HetNets)
 - mmWave
 - Massive MIMO
 - Smarter devices



Multi-cell Processing / Cooperation


- The BSs are connected via Backhaul networks.
- CoMP:
 - BSs share channel state information (CSI)
 - Perform beamforming and power control
 - Downlink cooperation among BSs



- **What about uplink cooperation among UEs?**


Hybrid D2D-infrastructure cooperation

- Uplink communications
 - Two close UEs (mobiles) can “hear” each other
 - They can communicate directly (D2D)or
 - Exchange their information and perform uplink beamforming (hybrid)



Hybrid D2D-infrastructure cooperation

- Uplink communications
 - Two close UEs (mobiles) can “hear” each other
 - They can communicate directly (D2D)or
 - Exchange their information and perform uplink beamforming (hybrid)




Can be applied in
small cells /
HetNets as well

Comparison among 3 transmission modes


- Half-duplex transmissions
- Consider transmissions on the same frequency band

Resource partitioning
(LTE and LTE-A)




- Each UE transmits on a different time slot

Concurrent trans.
with SIC



- Both UEs transmit at the same time
- BS performs SIC


Cooperative trans.
(TD and D2D)




- Two UEs cooperate to transmit to the BS.
- 3 phase transmission
- Virtual beamforming
- Advance processing

3 transmission modes over a frame


Resource partitioning (LTE and LTE-A)



Concurrent trans. with SIC




Cooperative transmission (TD and D2D)



Outline for the rest of the talk

- User-assisted cooperative transmission
 - Transmit signal design
 - Decoding techniques
 - Achievable rate region
- Deployment in cellular networks
- Reliability/Outage performance

Channel Model



$$\left. \begin{array}{l} Y_{12} = h_{12}X_{10} + Z_1 \\ Y_1 = h_{10}X_{10} + Z_{31} \end{array} \right| \left. \begin{array}{l} Y_{21} = h_{21}X_{20} + Z_2 \\ Y_2 = h_{20}X_{20} + Z_{32} \end{array} \right| \begin{array}{l} Y_3 = h_{10}X_{11} \\ \quad + h_{20}X_{22} + Z_{33} \end{array}$$

Rayleigh block fading

$$h_{ij} = g_{ij}e^{j\kappa\theta_{ij}}$$



Complex Gaussian noise

$$Z \sim \mathcal{CN}(0, 1)$$


Transmission Scheme

$$w_1 \rightarrow (w_{10}, w_{11})$$

$$w_2 \rightarrow (w_{20}, w_{22})$$



Transmit signal design



Transmit signals

$$X_{10} = \sqrt{\rho_{10}}U_{10}(w_{10}) \quad X_{20} = \sqrt{\rho_{20}}U_{20}(w_{20})$$




$$X_{11} = \sqrt{\rho_{11}}V_{11}(w_{11}) + \sqrt{\rho_1}S(w_{10}, w_{20})$$

$$X_{22} = \sqrt{\rho_{22}}V_{22}(w_{22}) + \sqrt{\rho_2}S(w_{10}, w_{20})$$

Power constraints

$$\alpha_1\rho_{10} + \alpha_3(\rho_{11} + \rho_1) \leq P_1, \quad \alpha_2\rho_{20} + \alpha_3(\rho_{22} + \rho_2) \leq P_2$$

Decoding and Rate region



At **UE₂**: $Y_{12} \rightarrow \tilde{w}_{10}$

$$R_{12} \leq \alpha_1 \mathcal{C}(g_{12}^2 \rho_{10}) = J_1$$

At **UE₂**: $Y_{21} \rightarrow \tilde{w}_{20}$

$$R_{21} \leq \alpha_1 \mathcal{C}(g_{21}^2 \rho_{20}) = J_2$$

At **BS**: $(Y_1, Y_2, Y_3) \rightarrow (\hat{w}_1, \hat{w}_2)$

$$R_{11} \leq \alpha_3 \mathcal{C}(g_{10}^2 \rho_{11}) = J_3,$$


$$R_{22} \leq \alpha_3 \mathcal{C}(g_{20}^2 \rho_{22}) = J_4,$$

$$R_{11} + R_{22} \leq \alpha_3 \mathcal{C} \left(\begin{array}{l} R_1 \leq J_1 + J_3, \\ R_2 \leq J_2 + J_4 \end{array} \right)$$

$$R_1 + R_{22} \leq \alpha_1 \mathcal{C} \left(\begin{array}{l} R_1 + R_2 \leq J_1 + J_2 + J_5, \\ R_1 + R_2 \leq J_8 \end{array} \right) J_7$$

$$R_1 + R_2 \leq \alpha_1 \mathcal{C}(g_{10}'^2 \rho_{11}) + \alpha_2 \mathcal{C}(g_{20}'^2 \rho_{20}) + \alpha_3 \zeta = J_8, \quad \zeta = \mathcal{C}(g_{10}'^2 \rho_{11} + g_{20}'^2 \rho_{22} + (g_{10} \sqrt{\rho_1} + g_{20} \sqrt{\rho_2})^2).$$

Achievable Rate Region




A. Abu Al Haija and M. Vu, "A Half-Duplex Cooperative Scheme with Partial Decode-Forward Relaying" IEEE Int'l Symp. on Information Theory, July 2011.

Talk Outline


- User-assisted cooperative transmission
- Deployment in cellular networks
 - Deployment policy
 - Out-of-cell interference
 - Throughput performance gain
- Reliability/Outage performance

Deployment in Cellular Networks

- Deployment of user-assisted relaying
 - An idle user helps relay data of an active user
- Study **network-wide impact** of user-assisted relaying
 - On throughput, outage, coverage




Stochastic Geometry Model



- Factors to consider:
 - When should a user cooperate?
 - What is the effect on network interference and overall performance?
- Performance evaluation:
 - Analysis using stochastic geometry tools
 - Verify analysis with simulation

System Model




- Consider a multi-cell system
 - Each cell has a single base station
 - Reuse factor 1 in the whole network
 - An active user can relay through the closest idle user

Channel Model & Relaying Scheme

T : Transmission Time


$$\alpha_1, \alpha_2 \in [0, 1], \alpha_1 + \alpha_2 = 1$$



- User-assisted relaying:
 - Two phase transmission scheme
 - Flat fading over the two phase period
- **Active user (source S):** uses superposition coding
- **Relay user (relay R):** transmit coherently with the source in 2nd phase
- **Base station (destination D):** utilizes received signals in both phases to decode the message

Network Geometric Model

- We use stochastic geometry to model the network
- Active UEs as a PPP with density λ_1
- Idle UEs as a PPP with density λ_2



Cooperation Policies

- Ideal policy (E_1):

- Perfect knowledge of source channel state information
- Perfect knowledge of the interference

$$E_1 \simeq \left\{ \frac{g_{sr}r_2^{-\alpha}}{\mathcal{I}_r^2} \geq \frac{g_{sd}r_1^{-\alpha}}{\mathcal{I}_d^2} \right\}.$$

- Pure geometric policy (E_2):


- Only knows the distances
- Practical for fast fading channels

$$E_2 = \{r_1 \geq r_2, D \leq r_1\}.$$


- Hybrid fading and geometric policy (E_3):

- Knows both small and large scale fading but not the interference
- Applicable for slow fading channels

$$E_3 = \{g_{sd}r_1^{-\alpha} \leq g_{sr}r_2^{-\alpha}, D \leq r_1\}.$$




Cooperation Probability





Interference Model


- We need to characterize the interference at
 - Relay user during 1st phase
 - Base station during 1st phase
 - Base station during 2nd phase
- Stochastic geometry and PPP
 - Can provide analytic expression for moments
 - Fails to provide the exact distribution
- Consider a Gamma distribution model
 - Fit the first two moments of interference distribution
 - Approximately fit empirical data




Fit of Gamma Distribution




Interference Model: Effect of Gamma Distribution




Throughput vs. Distance to Relay



Data rate gain vs. active user location



Average data rate gain vs. idle to active ratio




H. ElKotby and M. Vu, "Interference and Throughput Analysis of Uplink User-Assisted Relaying in Cellular Networks," IEEE 25th Int'l Symp. on Personal, Indoor and Mobile Radio Commun. (PIMRC), Sep 2014.

Talk Outline

- User-assisted cooperative transmission
- Deployment in cellular networks
- Reliability/Outage performance
 - Outage at the UEs and BS
 - Common outage
 - Individual outage


Outage Probabilities

- Full CSI at Rx and limited at Tx.
- Consider both individual and common outage probabilities
 - Common outage: either one or both UEs information is in outage.
 - Individual outage: one UE information is in outage regardless of the other UE information.
- The outage probabilities in Rayleigh fading channels




Outage Probability: LTE and Concurrent Trans.

LTE & LTE-A




Rates: $R_1 \leq A_1$, $R_2 \leq A_2$,


Individual Outage (UE₁)




Individual Outage (UE₂)



Common Outage




Concurrent trans. with SIC




Rates: $R_1 \leq B_1$, $R_2 \leq B_2$,

$R_1 + R_2 \leq B_3$


Individual Outage (UE₁)



Individual Outage (UE₂)




Common Outage




Cooperative Transmission Outages

Outage at UE2




No Outage at UE2 but at outage UE1




No Outage at both UEs but outage at the BS

Coop. and/or private part



Outage Analysis for Cooperative Transmission



- Outage can occur at **UEs** in addition to the BS
 - But cooperative links are stronger than direct links
 - Hence outage at UEs is small (insignificant)
 - Cooperation reduces outage probability
- Superposition coding
 - Outage for **cooperative and private** parts

Outage at the BS (if no outage at UEs)


$R_{10} \leq J_4 - R_p$, $R_{20} \leq J_5 - R_p$, $R_{10} + R_{20} \leq J_6 - R_p$, Cooperative rates const.

where $R_p = R_{11} + R_{22}$

$R_{12} \leq J_1$, $R_{22} \leq J_2$, $R_{12} + R_{22} \leq J_3$,


Private rates const.

Cooperative parts outage: Outage of any cooperative part leads to an outage at both private parts because of superposition encoding




Common and individual Outages for private parts (no outage for the coop. parts)


Individual Outage (UE1)






Individual Outage (UE2)





Common Outage



Summary of the Outage Analyses



*Resource Part. LTE & LTE-A	*Concurrent Trans. with SIC	*Coop. Trans. using D2D
No message splitting	No message splitting	- Coop. & private message splitting (outage for each part) - Additional outage at UEs
Conventional coding	Conventional coding	Superposition Coding
Outage at the BS only	Outage at the BS only	Outage at the UEs & the BS
Rates at BS: $R_1 \leq A_1, R_2 \leq A_2,$ 	Rates at BS: $R_1 \leq B_1, R_2 \leq B_2, \\ R_1 + R_2 \leq B_3$ 	- Outage at UE1 or UE2 leads to a common outage - No outage at UEs but at BS - Coop. Rates $R_{10} \leq J_4, R_{20} \leq J_5, R_{10} + R_{20} \leq J_6,$ - Private Rates $R_{12} \leq J_1, R_{22} \leq J_2, R_{12} + R_{22} \leq J_3,$ 

Outage Probability of User-assisted Relaying





A. Abu Al Haija and M. Vu, “**Outage Analysis for Half-Duplex Partial Decode-Forward Relaying over Fading Channel**,” IEEE Globecom, Dec 2014.

Outage Probabilities of Both Users Cooperating



Outage Rate Regions at 1% Outage Probability



A.A.Al Haija and M. Vu, "Spectral Efficiency and Outage Performance for Hybrid D2D-Infrastructure Uplink Cooperation," under review IEEE Trans. on Wireless Comm.

Conclusion

- User-assisted cooperative relaying for uplink communication
 - Utilizes hybrid D2D-infrastructure cooperation
 - Has advanced signal design and decoding
 - Employs partial decode-forward relaying and joint decoding at BS
- Cooperation improves **both** the data rate and reliability
 - Compared to current LTE implementation
- Network deployment shows significant performance gain
 - Average rate gain up to 50%, max gain up to 200%
 - Suitable for crowded metropolitan areas and small cells

Relevant Publications

- A. Abu Al Haija and M. Vu, "Outage Analysis for Half-Duplex Partial Decode-Forward Relaying over Fading Channel," IEEE Conf. on Global Comm. (Globecom), Dec. 2014.
- H. ElKotby and M. Vu, "Interference and Throughput Analysis of Uplink User-Assisted Relaying in Cellular Networks," IEEE 25th Int'l Symp. on Personal, Indoor and Mobile Radio Commun. (PIMRC), Washington DC, Sep 2014.
- A. Abu Al Haija and M. Vu, "Spectral Efficiency and Outage Performance for Hybrid D2D-Infrastructure Uplink Cooperation," submitted to IEEE Trans. on Wireless Comm., Mar 2014.
- H. ElKotby and M. Vu, "Uplink User-Assisted Relaying Deployment in Cellular Networks," submitted to IEEE Trans. on Wireless Comm., Aug. 2014.
- A. Abu Al Haija and M. Vu, "Outage Analysis for Coherent Decode-Forward Relaying over Rayleigh Fading Channels," submitted to IEEE Trans. on Comm., Aug. 2014.
- A. Abu Al Haija and M. Vu, "Rate Maximization for Half-Duplex Multiple Access with Cooperating Transmitters" IEEE Trans. Comm., vol. 61, no. 9, pp.3620-3634, Sept . 2013.
- A. Abu Al Haija and M. Vu, "Outage Analysis for Uplink Mobile-to-Mobile Cooperation," IEEE Conf. on Global Comm. (Globecom), Dec 2013.
- A. Abu Al Haija and M. Vu, "Throughput-Optimal Half-Duplex Cooperative Scheme with Partial Decode-Forward Relaying" IEEE ICC, June 2011.
- A. Abu Al Haija and M. Vu, "A Half-Duplex Cooperative Scheme with Partial Decode-Forward Relaying" IEEE ISIT, July 2011.

More information

- Research group: **Tufts LiNKS**

Laboratory for communication in Networked Systems

<http://links.ece.tufts.edu>

- My webpage <http://www.eecs.tufts.edu/~maivu/>
- Email maivu@ece.tufts.edu